

PSI Part#	Width	Length	Description	LPR	RPC	Lbs.	Hue
SLANT0100	1.85"	3.156"	Antonson	900	12	18	r/y
SLANT0100B	1.85"	3.156"	Antonson Blank	900	12	18	
SLANT0101	1.85"	3.96"	Antonson	750	12	18	r/y
SLANT0101B	1.85"	3.96"	Antonson Blank	750	12	18	
SLANT0101P	1.85"	3.96"	Antonson Perfed	750	12	18	r/y
SLANT0101BP	1.85"	3.96"	Antonson Blank Perfed	750	12	18	
SLANT0102	1.85"	3.96"	Antonson Deli Prepack	750	12	18	r/y
SLANT0102B	1.85"	3.96"	Antonson Deli Prepack Blank	750	12	18	
SLANT0102P	1.85"	3.96"	Antonson Deli Prepack Perfed	750	12	18	r/y
SLANT0102BP	1.85"	3.96"	Antonson Deli Prepack Blank Perfed	750	12	18	
SLANT0103P	1.85"	4.97"	Antonson Perfed	600	12	18	r/y
SLANT0103BP	1.85"	4.97"	Antonson Blank Perfed	600	12	18	
SLANT0104	1.85"	2.44"	Antonson 423/523 Deli Short	1160	12	18	r/y
SLANT0104B	1.85"	2.44"	Antonson 423/523 Deli Short Blank	1160	12	18	
SLANT0105C	1.85"	2930"	Antonson Continuous Strip	Cont.	12	18	
SLBER0201	.9375"	2.56"	Avery 1770 Non-Thermal	1000	24	17	red
SLBER0201B	.9375"	2.56"	Avery 1770 Non-Thermal Blank	1000	24	17	
SLBER0202	1.5"	2.813"	Avery A-100	1000	15	17	red
SLBER0202B	1.5"	2.813"	Avery A-100 Blank	1000	15	17	
SLBER0203	.9376"	4.44"	Avery 10039-2 Non-Thermal	600	24	15	red
SLBER0203B	.9376"	4.44"	Avery 10039-2 Non-Thermal Blank	600	24	15	
SLBER0204B	49mm	40mm	Avery/Berkel Blank	1700	12	15	
SLBER0205	49mm	65mm	Avery/Berkel	1000	12	15	r/y
SLBER0205B	49mm	65mm	Avery/Berkel Blank	1000	12	15	
SLBER0205P	49mm	65mm	Avery/Berkel Perfed	1000	12	15	r/y
SLBER0205BP	49mm	65mm	Avery/Berkel Blank Perfed	1000	12	15	
SLBER0206	49mm	96mm	Avery/Berkel	700	12	15	r/y
SLBER0206B	49mm	96mm	Avery/Berkel Blank	700	12	15	
SLBER0206P	49mm	96mm	Avery/Berkel Perfed	700	12	15	r/y
SLBER0206BP	49mm	96mm	Avery/Berkel Blank Perfed	700	12	15	
SHBER0206	49mm	96mm	Avery/Berkel Safe Handling	700	12	15	r/y/blk
SHBER0207	49mm	96mm	Avery/Berkel Safe Handling Only	700	12	15	black
SLBER0208	49mm	125mm	Avery/Berkel	500	12	15	r/y
SLBER0208B	49mm	125mm	Avery/Berkel Blank	500	12	15	
SLBER0208P	49mm	125mm	Avery/Berkel Perfed	500	12	15	r/y
SLBER0208BP	49mm	125mm	Avery/Berkel Blank Perfed	500	12	15	
SHBER0208	49mm	125mm	Avery/Berkel Safe Handling	500	12	15	r/y/blk
SHBER0209	49mm	125mm	Avery/Berkel Safe Handling Only	500	12	15	black
SLBER0210	49mm	160mm	Avery/Berkel	380	12	15	r/y
SLBER0210B	49mm	160mm	Avery/Berkel Blank	380	12	15	
SLBER0210P	49mm	160mm	Avery/Berkel Perfed	380	12	15	r/y
SLBER0210BP	49mm	160mm	Avery/Berkel Blank Perfed	380	12	15	
SLBER0211C	51mm	1860"	Avery/Berkel 623 LS Continuous Strip	Cont.	12	16	
SLBER0212	49mm	40mm	Berkel 623 LS Non-UPC	1200	12	15	r/gray
SLBER0212B	49mm	40mm	Berkel 623 LS Non-UPC Blank	1200	12	15	
SLBER0213	54mm	50mm	Berkel 623 LS UPC	1000	12	18	r/b
SLBER0213B	54mm	50mm	Berkel 623 LS UPC Blank	1000	12	18	
SLBER0214	54mm	50mm	Berkel 623 LS Non-UPC	1000	12	18	r/b
SLBER0214B	54mm	50mm	Berkel 623 LS Non-UPC Blank	1000	12	18	
SLBER0215	54mm	65mm	Berkel 623 LS Non-UPC	750	12	18	r/gray
SLBER0215B	54mm	65mm	Berkel 623 LS Non-UPC Blank	750	12	18	
SLBER0216	54mm	65mm	Berkel 623 LS UPC	750	12	18	r/gray
SLBER0216B	54mm	65mm	Berkel 623 LS UPC Blank	750	12	18	
SHBER0217	49mm	105mm	Berkel 623 LS Safe Handling	380	12	15	r/gray
SLBER0217B	49mm	105mm	Berkel 623 LS Blank	380	12	15	

PSI Part#	Width	Length	Description	LPR	RPC	Lbs.	Hue
SHBER0218	49mm	76mm	Berkel CX-17 Safe Handling	525	12	12	black
SLBER0218B	49mm	76mm	Berkel CX-17 Blank	525	12	12	
SLBER0219B	49mm	40mm	Berkel CX-17/20/30 Blank	1000	12	12	
SLBER0220	49mm	65mm	Berkel CX-17/20/30	625	12	12	r/y
SLBER0220B	49mm	65mm	Berkel CX-17/20/30 Blank	625	12	12	
SLBER0220P	49mm	65mm	Berkel CX-17/20/30 Perfed	625	12	12	r/y
SLBER0220BP	49mm	65mm	Berkel CX-17/20/30 Blank Perfed	625	12	12	
SLBER0221	49mm	96mm	Berkel CX-17/20/30	425	12	12	r/y
SLBER0221B	49mm	96mm	Berkel CX-17/20/30 Blank	425	12	12	
SLBER0221P	49mm	96mm	Berkel CX-17/20/30 Perfed	425	12	12	r/y
SLBER0221BP	49mm	96mm	Berkel CX-17/20/30 Blank Perfed	425	12	12	
SHBER0221	49mm	96mm	Berkel CX-17/20/30 Safe Handling	425	12	12	r/y/blk
SHBER0222	49mm	96mm	Berkel CX-17/20/30 Safe Handling Only	425	12	12	black
SLBER0223	49mm	125mm	Berkel CX-17/20/30	325	12	12	r/y
SLBER0223B	49mm	125mm	Berkel CX-17/20/30 Blank	325	12	12	
SLBER0223P	49mm	125mm	Berkel CX-17/20/30 Perfed	325	12	12	r/y
SLBER0223BP	49mm	125mm	Berkel CX-17/20/30 Blank Perfed	325	12	12	
SHBER0223	49mm	125mm	Berkel CX-17/20/30 Safe Handling	325	12	12	r/y/blk
SHBER0224	49mm	125mm	Berkel CX-17/20/30 Safe Handling Only	325	12	12	black
SLBER0225	49mm	160mm	Berkel CX-17/20/30	250	12	12	r/y
SLBER0225B	49mm	160mm	Berkel CX-17/20/30 Blank	250	12	12	
SLBER0225P	49mm	160mm	Berkel CX-17/20/30 Perfed	250	12	12	r/y
SLBER0225BP	49mm	160mm	Berkel CX-17/20/30 Blank Perfed	250	12	12	
SLBER0226C	51mm	1560"	Berkel CX-17/20/30 Continuous Strip	Cont.	12	13	
SLBER0227	1.25"	3"	Berkel DP-1 Non-Thermal	1000	12	13	y/blk
SLBER0227B	1.25"	3"	Berkel DP-1 Non-Thermal Blank	1000	12	13	
SLBER0228	1.25"	3"	Berkel DP-1 Non-Thermal Thank You	1000	12	13	r/blk
SLBER0228B	1.25"	3"	Berkel DP-1 Non-Thermal Thank Blank	1000	12	13	
SLBER0229	58mm	30mm	Berkel GX250	1000	12	12	r/y
SLBER0229B	58mm	30mm	Berkel GX250 Blank	1000	12	12	
SLBER0230	58mm	60mm	Berkel GX250	520	12	12	r/y
SLBER0230B	58mm	60mm	Berkel GX250 Blank	520	12	12	
SLBER0231	58mm	75mm	Berkel GX250	410	12	12	r/y
SLBER0231B	58mm	75mm	Berkel GX250 Blank	410	12	12	
SHBER0231	58mm	75mm	Berkel GX250 Safe Handling Only	410	12	12	black
SLBER0232C	58mm	1250"	Berkel GX250 Continuous Strip	Cont.	12	12	
SLBER0233C	58mm	2600"	Berkel M/MP Series Continuous Strip	Cont.	12	12	
SLBER0234B	58mm	40mm	Berkel M/MP Series Blank	1550	12	12	
SLBER0235B	58mm	65mm	Berkel M/MP Series Blank	1000	12	12	
SLBER0235BP	58mm	65mm	Berkel M/MP Series Perfed	1000	12	12	
SLBER0236B	58mm	75mm	Berkel M/MP Series Blank	850	12	12	
SLBER0236BP	58mm	75mm	Berkel M/MP Series Perfed	850	12	12	
SLBER0237B	58mm	100mm	Berkel M/MP Series Blank	650	12	12	
SLBER0237BP	58mm	100mm	Berkel M/MP Series Perfed	650	12	12	
SLBER0238B	58mm	160mm	Berkel M/MP Series Blank	410	12	12	
SLBER0238BP	58mm	160mm	Berkel M/MP Series Perfed	410	12	12	
SLBER0239	1.25"	3"	Berkel P-502	1500	12	18	black
SLBER0240	1.25"	3"	Berkel P-500/501/800 Non-Thermal 1-5/8"	1500	12	18	y/blk
SLBER0240B	1.25"	3"	Berkel P-500/501/800 Non-Thermal 1-5/8"	1500	12	18	
SLBER0241	1.25"	3"	Berkel P-500/501/800 Non-Thermal 3" Cor	1000	12	13	y/blk
SLBER0241B	1.25"	3"	Berkel P-500/501/800 Non-Thermal 3" Cor	1000	12	13	
SLBER0242	1.25"	3"	Berkel P-500/502/522 Thermal 1-5/8" Core	1500	12	18	y/blk
SLBER0242B	1.25"	3"	Berkel P-500/502/522 Thermal 1-5/8" Core	1500	12	18	
SLBER0243	1.25"	3"	Berkel P-500/502 Date 3" Core	750	12	18	y/blk
SLBER0243B	1.25"	3"	Berkel P-500/502 Date 3" Core Blank	750	12	18	

PSI Part#	Width	Length	Description	LPR	RPC	Lbs.	Hue
SLBIZ0300B	58mm	43mm	Bizerba Blank	1000	12	13	
SLBIZ0301B	58mm	60mm	Bizerba Blank	725	12	13	
SLBIZ0302C	58mm	1704"	Bizerba Continuous Strip	Cont.	12	13	
SLCAS0400	58mm	30mm	CAS LP-1000 Non-UPC	1000	12	12	r/b
SLCAS0401	58mm	40mm	CAS LP-1000 UPC	700	12	12	
SHCAS0402	58mm	50mm	CAS LP-1000 Non-UPC Safe Handling	600	12	12	r/b
SLCAS0402B	58mm	50mm	CAS LP-1000 Blank	600	12	12	r/b
SLCAS0403	58mm	60mm	CAS LP-1000 UPC Ingredient	500	12	12	r/b
SLCAS0403B	58mm	60mm	CAS LP-1000 Blank	500	12	12	
SHCAS0404	58mm	60mm	CAS LP-1000 UPC Safe Handling	500	12	12	r/b
SLCAS0404B	58mm	60mm	CAS LP-1000 UPC Blank	500	12		
SLDIG0500BFO	40mm	23mm	Digi Red Fluorescent Da-Glo Wound Out	2500	15	15	
SLDIG0500BFI	40mm	23mm	Digi Red Fluorescent Da-Glo Wound In	2500	15	15	
SLDIG0500BO	40mm	23mm	Digi Blank Wound Out	2500	15	15	
SLDIG0500BI	40mm	23mm	Digi Blank Wound In	2500	15	15	
SLDIG0501	2.65"	1.78"	Digi 1000 UPC	4000	3	15	r/b
SLDIG0501B	2.65"	1.78"	Digi 1000 UPC Blank	4000	3	15	
SLDIG0502	2.65"	1.78"	Digi 2000 UPC	7000	3	28	r/b
SLDIG0502B	2.65"	1.78"	Digi 2000 UPC Blank	7000	3	28	
SLDIG0503B	60mm	175mm	Digi BL-8000 Blank	757	6	15	
SLDIG0504B	40mm	39mm	Digi BP-82 Blank	5000	5	13	
SLDIG0505B	40mm	92mm	Digi DP-110 Blank	650	15	15	
SLDIG0506	40mm	120mm	Digi DP-110	500	20	20	r/y
SLDIG0506B	40mm	120mm	Digi DP-110 Blank	500	20	20	
SLDIG0506P	40mm	120mm	Digi DP-110 Perfed	500	20	20	r/y
SLDIG0506BP	40mm	120mm	Digi DP-110 Blank Perfed	500	20	20	
SLDIG0507	60mm	43mm	Digi DP-25/70/120 1.5" Core	1500	15	22	r/b
SLDIG0507B	60mm	43mm	Digi DP-25/70/120 Blank 1.5" Core	1500	15	22	
SLDIG0508	60mm	55mm	Digi DP-25/70/120 1.5" Core	1100	15	22	r/b
SLDIG0508B	60mm	55mm	Digi DP-25/70/120 Blank 1.5" Core	1100	15	22	
SLDIG0509	60mm	80mm	Digi DP-25/70/120 1.5" Core	810	15	22	r/b
SLDIG0509B	60mm	80mm	Digi DP-25/70/120 Blank 1.5" Core	810	15	22	
SHDIG0509	60mm	80mm	Digi DP-25/70/120 Safe Handling 1.5" Core	810	15	22	r/b
SLDIG0510	60mm	95mm	Digi DP-120/121 SM-25/70 1.5" Core	665	15	22	r/b
SLDIG0510B	60mm	95mm	Digi DP-120/121 SM-25/70 1.5" Core Blank	665	15	22	
SLDIG0510BP	60mm	95mm	Digi DP-120/121 SM-25/70 1.5" Core Blank	665	15	22	
SLDIG0510BTP	60mm	95mm	Digi DP-120/121 SM-25/70 1.5" Core Blank	665	15	22	
SHDIG0510	60mm	95mm	Digi DP-120/121 SM-25/70 1.5" Core	665	15	22	r/b
SLDIG0511	60mm	95mm	Digi DP-120/121 SM-25/70 1.5" Core Red	665	15	22	red
SLDIG0512	60mm	95mm	Digi DP-120/121 SM-25/70 1.5" Core Blue	665	15	22	blue
SLDIG0513B	60mm	110mm	Digi DP-120/121 SM-25/70 Blank	575	15	22	
SLDIG0513BP	60mm	110mm	Digi DP-120/121 SM-25/70 Blank Perfed	575	15	22	
SLDIG0514B	60mm	120mm	Digi DP-120/121 SM-25/70 Blank	575	15	22	
SLDIG0515B	60mm	133mm	Digi DP-120/121 SM-25/70 Blank	475	15	22	
SLDIG0516	60mm	43mm	Digi DP-120 SM-90	1050	15	20	r/b
SLDIG0516B	60mm	43mm	Digi DP-120 SM-90 Blank	1050	15	20	
SLDIG0517	60mm	55mm	Digi DP-120 SM-90	830	15	20	r/b
SLDIG0517B	60mm	55mm	Digi DP-120 SM-90 Blank	830	15	20	
SLDIG0518	60mm	80mm	Digi DP-120 SM-90	580	15	19	r/b
SLDIG0518B	60mm	80mm	Digi DP-120 SM-90 Blank	580	15	19	
SHDIG0518	60mm	80mm	Digi DP-120 SM-90 Safe Handling	580	15	19	r/b
SLDIG0519	60mm	95mm	Digi DP-120 SM-90	500	15	20	r/b
SLDIG0519B	60mm	95mm	Digi DP-120 SM-90 Blank	500	15	20	
SLDIG0519BP	60mm	95mm	Digi DP-120 SM-90 Blank Perfed	500	15	20	
SLDIG0519BTP	60mm	95mm	Digi DP-120 SM-90 Blank T-Perfed	500	15	20	

PSI Part#	Width	Length	Description	LPR	RPC	Lbs.	Hue
SHDIG0519	60mm	95mm	Digi DP-120 SM-90 Safe Handling	500	15	20	r/b
SLDIG0520B	60mm	110mm	Digi DP-120/121 SM-90 Blank	425	15	20	
SLDIG0521B	60mm	120mm	Digi DP-120/121 SM-90 Blank	400	15	22	
SLDIG0522B	60mm	125mm	Digi DP-120/121 SM-90 Blank	375	15	22	
SLDIG0523	60mm	80mm	Digi DPS-2600/6000 1.5" Core	2200	3	13	r/b
SLDIG0523B	60mm	80mm	Digi DPS-2600/6000 Blank 1.5" Core	2200	3	13	
SHDIG0523	60mm	80mm	Digi DPS-2600/6000 Safe Handling 1.5" Core	2200	3	13	r/b
SLDIG0524	60mm	80mm	Digi DPS-2600/6000 3" Core	1800	3	13	r/b
SLDIG0524B	60mm	80mm	Digi DPS-2600/6000 Blank 3" Core	1800	3	13	
SHDIG0524	60mm	80mm	Digi DPS-2600/6000 Safe Handling 3" Core	1800	3	13	r/b
SLDIG0525	60mm	95mm	Digi DPS-2600/6000 1.5" Core	1800	3	13	r/b
SLDIG0525B	60mm	95mm	Digi DPS-2600/6000 Blank 1.5" Core	1800	3	13	
SHDIG0525	60mm	95mm	Digi DPS-2600/6000 Safe Handling 1.5" Core	1800	3	13	r/b
SLDIG0526	60mm	95mm	Digi DPS-2600/6000 3" Core	1500	3	13	r/b
SLDIG0526B	60mm	95mm	Digi DPS-2600/6000 Blank 3" Core	1500	3	13	
SHDIG0526	60mm	95mm	Digi DPS-2600/6000 Safe Handling 3" Core	1500	3	13	r/b
SLDIG0527	60mm	43mm	Digi DPS-6000/6084 UPC 1.5" Core	4000	3	13	r/b
SLDIG0527B	60mm	43mm	Digi DPS-6000/6084 Blank 1.5" Core	4000	3	13	
SLDIG0528	60mm	43mm	Digi DPS-6000/6084 UPC 3" Core	3240	3	13	r/b
SLDIG0528B	60mm	43mm	Digi DPS-6000/6084 Blank 3" Core	3240	3	13	
SLDIG0529	60mm	55mm	Digi DPS-6000/6084 UPC 1.5" Core	3000	3	13	r/b
SLDIG0529B	60mm	55mm	Digi DPS-6000/6084 Blank 1.5" Core	3000	3	13	
SLDIG0530	60mm	55mm	Digi DPS-6000/6084 UPC 3" Core	2400	3	13	r/b
SLDIG0530B	60mm	55mm	Digi DPS-6000/6084 Blank 3" Core	2400	3	13	
SLDIG0531	40mm	46mm	Digi SM-15 Non-UPC Red	600	30	17	red
SLDIG0532	40mm	46mm	Digi SM-15 Non-UPC Green	600	30	17	green
SLDIG0531B	40mm	46mm	Digi SM-15 Blank	600	30	17	
SLDIG0533	40mm	62mm	Digi SM-15 UPC Red	500	30	13	red
SLDIG0534	40mm	62mm	Digi SM-15 UPC Green	500	30	13	green
SLDIG0535	40mm	62mm	Digi SM-15 UPC Thank You Red	500	30	13	red
SLDIG0536	40mm	62mm	Digi SM-15 UPC Thank You Green	500	30	13	green
SLDIG0535B	40mm	62mm	Digi SM-15 Blank	500	30	13	
SLDIG0537	40mm	92mm	Digi SM-15i	350	25	18	blue
SLDIG0537B	40mm	92mm	Digi SM-15i Blank	350	25	18	
SLDIG0537P	40mm	92mm	Digi SM-15i Perfed	350	25	18	blue
SLDIG0537BP	40mm	92mm	Digi SM-15i Blank Perfed	350	25	18	
SLDIG0538	40mm	62mm	Digi SM-25/40/60/70 UPC Red	1000	20	21	red
SLDIG0539	40mm	62mm	Digi SM-25/40/60/70 UPC Green	1000	20	21	green
SLDIG0540	40mm	62mm	Digi SM-25/40/60/70 UPC Thank You Red	1000	20	21	red
SLDIG0541	40mm	62mm	Digi SM-25/40/60/70 UPC Thank You Green	1000	20	21	green
SLDIG0540B	40mm	62mm	Digi SM-25/40/60/70 Blank	1000	20	21	
SLDIG0542P	40mm	120mm	Digi SM-25/60i/70 Perfed	500	20	20	r/y
SLDIG0542BP	40mm	120mm	Digi SM-25/60i/70 Blank Perfed	500	20	20	
SLDIG0543	40mm	62mm	Digi SM-90 UPC Red	725	30	13	red
SLDIG0544	40mm	62mm	Digi SM-90 UPC Green	725	30	13	green
SLDIG0545	40mm	62mm	Digi SM-90 UPC Thank You Red	725	30	13	red
SLDIG0546	40mm	62mm	Digi SM-90 UPC Thank You Green	725	30	13	green
SLDIG0545B	40mm	62mm	Digi SM-90 Blank	725	30	13	
SLEXA0600	2.9687	1.5626"	Exact 950 Prepack UPC	6000	5	35	r/y
SLEXA0600B	2.9687	1.5626"	Exact 950 Blank	6000	5	35	
SHEXA0601	2.9687	2.6562"	Exact 950 UPC	3500	5	31	r/y
SLEXA0602	2.9687	1.5626"	Exact 960 UPC	5500	5	35	r/y
SLEXA0602B	2.9687	1.5626"	Exact 960 Blank	5500	5	35	
SLEXA0603	2.9687	1.5626"	Exact 960 UPC 4 Line Ingredient	5500	5	35	r/y
SLEXA0603B	2.9687	1.5626"	Exact 960 Blank	5500	5	35	

PSI Part#	Width	Length	Description	LPR	RPC	Lbs.	Hue
SLEXA0604	2.9687	1.875"	Exact 960 Logo/UPC	4500	5	31	r/y
SLEXA0604B	2.9687	1.875"	Exact 960 Blank	4500	5	31	
SLEXA0605	2.9687	2.25"	Exact 960 Logo/UPC 4 Line Ingrid.	4500	5	31	r/y
SLEXA0605B	2.9687	2.25"	Exact 960 Blank	4500	5	31	
SLEXA0606	2.9687	2.6562"	Exact 960 Logo/UPC 8 Line Ingrid.	3500	5	32	r/y
SLEXA0606B	2.9687	2.6562"	Exact 960 Blank	3500	5	32	
SHEXA0606	2.9687	2.6562"	Exact 960 Logo/UPC Safe Handling	3500	5	32	r/y
SLEXA0607	64mm	59mm	Exact 971 Prepack	4000	5	35	r/y
SLEXA0607B	64mm	59mm	Exact 971 Blank	4000	5	35	
SHEXA0608	64mm	73mm	Exact 971 Prepack Safe Handling	2000	5	30	red
SLEXA0608B	64mm	73mm	Exact 971 Blank	2000	5	30	
SLEXA0609	64mm	85mm	Exact 971 Prepack	2800	5	30	r/y
SLEXA0609B	64mm	85mm	Exact 971 Blank	2800	5	30	
SLEXA0610	64mm	110mm	Exact 971 Bakery	2050	5	35	r/b
SLEXA0610B	64mm	110mm	Exact 971 Blank	2050	5	35	
SLEXA0611	64mm	47mm	Exact 972/973 Deli	800	12	15	r/b
SLEXA0611B	64mm	47mm	Exact 972/973 Blank	800	12	15	
SLEXA0612	64mm	59mm	Exact 972/973 Deli	625	12	15	r/b
SLEXA0612B	64mm	59mm	Exact 972/973 Blank	625	12	15	
SLEXA0613	64mm	85mm	Exact 972/973 Deli	450	12	15	r/b
SLEXA0613B	64mm	85mm	Exact 972/973 Blank	450	12	15	
SLEXA0614	64mm	110mm	Exact 972/973 Deli	350	12	15	r/b
SLEXA0614B	64mm	110mm	Exact 972/973 Blank	350	12	15	
SLEXA0615	64mm	59mm	Exact 972/973 Meat	625	12	15	r/b
SLEXA0615B	64mm	59mm	Exact 972/973 Blank	625	12	15	
SLEXA0616	64mm	85mm	Exact 972/973 Meat	450	12	15	r/b
SLEXA0616B	64mm	85mm	Exact 972/973 Blank	450	12	15	
SLEXA0617C	64mm	1584"	Exact 972/973 Continuous Strip	Cont.	12	15	
SLGLO0700	64mm	85mm	Global 220A	425	12	13	red
SLGLO0700B	64mm	85mm	Global 220A Blank	425	12	13	
SLGLO0701	64mm	67mm	Global 220 Notched	500	12	13	red
SLGLO0701B	64mm	67mm	Global 220 Notched Blank	500	12	13	
SHGLO0701	64mm	67mm	Global 220 Notched Safe Handling	500	12	13	red
SLGLO0702	64mm	85mm	Global 220B/650A	2500	5	18	red
SLGLO0702B	64mm	85mm	Global 220B/650A Blank	2500	5	18	
SLGLO0703	64mm	67mm	Global 650 Notched	3150	5	28	red
SLGLO0703B	64mm	67mm	Global 650 Notched Blank	3150	5	28	
SHGLO0703	64mm	67mm	Global 650 Notched Safe Handling	3150	5	28	red
SLGLO0704	64mm	59mm	Global Automator Exp. 220 UPC	625	12	13	r/y
SLGLO0704B	64mm	59mm	Global Automator Exp. 220 Blank	625	12	13	
SLGLO0705	64mm	47mm	Global Automator 650 UPC	4500	5	28	r/y
SLGLO0705B	64mm	47mm	Global Automator 650 Blank	4500	5	28	
SLGLO0706	64mm	59mm	Global Automator Exp. 650 UPC	3600	5	28	r/y
SLGLO0706B	64mm	59mm	Global Automator Exp. 650 Blank	3600	5	28	
SLGLO0707	64mm	37mm	Global Concentrator 220	1000	12	12	r/y
SLGLO0707B	64mm	37mm	Global Concentrator 220 Blank	1000	12	12	
SLGLO0708	64mm	47mm	Global Concentrator 220	800	12	13	r/y
SLGLO0708B	64mm	47mm	Global Concentrator 220 Blank	800	12	13	
SLHIS0800	2.625"	1.719"	Hi-Speed 100 UPC	6000	5	37	r/y
SLHIS0800B	2.625"	1.719"	Hi-Speed 100 Blank	6000	5	37	
SLHOB0900BF	1.5"	1"	Hobart Fluorescent Red	3000	10	12	red
SLHOB0901TP	2.4375	3.125"	Hobart 18BX Perfed	1900	4	15	r/b
SLHOB0901BTP	2.4375	3.125"	Hobart 18BX Blank Perfed	1900	4	15	
SLHOB0902	3.375"	1.125"	Hobart 18P Non-Thermal	2000	12	23	red
SLHOB0902B	3.375"	1.125"	Hobart 18P Non-Thermal Blank	2000	12	23	

PSI Part#	Width	Length	Description	LPR	RPC	Lbs.	Hue
SLHOB0903	3.375"	1.5625"	Hobart 18PC Non-Thermal	1500	12	23	r/b
SLHOB0903B	3.375"	1.5625"	Hobart 18PC Non-Thermal Blank	1500	12	23	
SLHOB0904	2.5"	1.6562"	Hobart 18VP	1250	16	21	r/b
SLHOB0904B	2.5"	1.6562"	Hobart 18VP Blank	1250	16	21	
SLHOB0905	2.5"	2.5625"	Hobart 18VP/1865 Style "D" Ingredient	850	16	22	r/b
SLHOB0905B	2.5"	2.5625"	Hobart 18VP/1865 Blank	850	16	22	
SHHOB0905	2.5"	2.5625"	Hobart 18VP/1865 "D" Safe Handling	850	16	22	r/b
SLHOB0906	2.5"	2.5625"	Hobart 18VP Style "U" Ingredient	850	16	22	r/b
SLHOB0906B	2.5"	2.5625"	Hobart 18VP Blank	850	16	22	
SHHOB0906	2.5"	2.5625"	Hobart 18VP "U" Safe Handling	850	16	22	r/b
SLHOB0907	2.5"	1.875"	Hobart 5000 TA 1.5" Core	5000	5	32	r/b
SLHOB0907B	2.5"	1.875"	Hobart 5000 TA Blank 1.5" Core	5000	5	32	
SLHOB0908	2.5"	1.875"	Hobart 5000 TA 3" Core	5000	5	32	r/b
SLHOB0908B	2.5"	1.875"	Hobart 5000 TA Blank 3" Core	5000	5	32	
SLHOB0909	2.5"	1.6562"	Hobart 5000 TC 1.5" Core	5000	5	25	r/b
SLHOB0909B	2.5"	1.6562"	Hobart 5000 TC Blank 1.5" Core	5000	5	25	
SLHOB0910	2.5"	1.6562"	Hobart 5000 TC 3" Core	5000	5	25	r/b
SLHOB0910B	2.5"	1.6562"	Hobart 5000 TC Blank 3" Core	5000	5	25	
SLHOB0911	2.5"	2.5625"	Hobart 5000 TE Style "D" Ingredient	3500	5	34	r/b
SLHOB0911B	2.5"	2.5625"	Hobart 5000 TE Blank	3500	5	34	
SHHOB0911	2.5"	2.5625"	Hobart 5000 TE "D" Safe Handling	3500	5	34	r/b
SLHOB0912	2.5"	2.5625"	Hobart 5000 TE Style "U" Ingredient	3500	5	34	r/b
SLHOB0912B	2.5"	2.5625"	Hobart 5000 TE Blank	3500	5	34	
SHHOB0912	2.5"	2.5625"	Hobart 5000 TE "U" Safe Handling	3500	5	34	r/b
SLHOB0913B	2.25"	1.75"	Hobart Quantum Blank	1600	16	35	
SLHOB0914B	2.25"	2.375"	Hobart Quantum Blank	1200	16	35	
SLHOB0915B	2.25"	3.0"	Hobart Quantum Blank	1000	16	35	
SLHOB0915BTP	2.25"	3.0"	Hobart Quantum Blank T-Perfed	1000	16	35	
SLHOB0916B	2.25"	3.5"	Hobart Quantum Blank	850	16	35	
SLHOB0917B	2.25"	4.5"	Hobart Quantum Blank	700	16	35	
SLHOB0917BTP	2.25"	4.5"	Hobart Quantum Blank T-Perfed	700	16	35	
SLHOB0918B	2.25"	6.0	Hobart Quantum Blank	525	16	35	
SLHOB0918BPD	2.25"	6.0	Hobart Quantum Blank Perfed Dome	525	16	35	
SLHOB0919C	2.25"	3240"	Hobart Quantum Continuous Strip	Cont.	16	35	
SLHOB0920C	2.25"	2250"	Hobart SP-80/1500 Continuous Strip	Cont.	16	22	
SLHOB0921	2.25"	1.75"	Hobart SP-80/1500 Style "J"	1275	16	22	r/b
SLHOB0921B	2.25"	1.75"	Hobart SP-80/1500 Blank	1275	16	22	
SLHOB0922	2.25"	3.0"	Hobart SP-80/1500 Style "K"	750	16	22	r/b
SLHOB0922B	2.25"	3.0"	Hobart SP-80/1500 Blank	750	16	22	
SHHOB0922	2.25"	3.0"	Hobart SP-80/1500 "K" Safe Handling	750	16	22	r/b
SLHOB0922P	2.25"	3.0"	Hobart SP-80/1500 "K" Perfed	750	16	22	r/b
SLHOB0922BP	2.25"	3.0"	Hobart SP-80/1500 Blank Perfed	750	16	22	
SHHOB0922P	2.25"	3.0"	Hobart SP-80/1500 "K" SH Perfed	750	16	22	r/b
SLHOB0923	2.25"	4.5"	Hobart SP-80/1500 Style "L"	500	16	22	r/b
SLHOB0923B	2.25"	4.5"	Hobart SP-80/1500 Blank	500	16	22	
SLHOB0923P	2.25"	4.5"	Hobart SP-80/1500 "L" Perfed	500	16	22	r/b
SLHOB0923BP	2.25"	4.5"	Hobart SP-80/1500 Blank Perfed	500	16	22	
SLHOB0924	2.25"	1.75"	Hobart SP-2-1500 Style "M"	2500	16	40	r/b
SLHOB0924B	2.25"	1.75"	Hobart SP-2-1500 Blank	2500	16	40	
SLHOB0925	2.25"	3.0"	Hobart SP-2-1500 Style "N"	1500	16	40	r/b
SLHOB0925B	2.25"	3.0"	Hobart SP-2-1500 Blank	1500	16	40	
SHHOB0925	2.25"	3.0"	Hobart SP-2-1500 "N" Safe Handling	1500	16	40	r/b
SLHOB0925P	2.25"	3.0"	Hobart SP-2-1500 "N" Perfed	1500	16	40	r/b
SLHOB0925BP	2.25"	3.0"	Hobart SP-2-1500 Blank Perfed	1500	16	40	
SHHOB0925P	2.25"	3.0"	Hobart SP-2-1500 "N" SH Perfed	1500	16	40	r/b

PSI Part#	Width	Length	Description	LPR	RPC	Lbs.	Hue
SLHOB0926	2.25"	4.5"	Hobart SP-2-1500 Style "P"	1000	16	40	r/b
SLHOB0926B	2.25"	4.5"	Hobart SP-2-1500 Blank	1000	16	40	
SLHOB0926P	2.25"	4.5"	Hobart SP-2-1500 "P" Perfed	1000	16	40	r/b
SLHOB0926BP	2.25"	4.5"	Hobart SP-2-1500 Blank Perfed	1000	16	40	
SLHOB0927	2.25"	3.0"	Hobart SP-1500 SP-2-1500 Style "R"	750	16	22	r/b
SLHOB0927B	2.25"	3.0"	Hobart SP-1500 SP-2-1500 Blank	750	16	22	
SLHOB0928	2.25"	4.5"	Hobart SP-1500 SP-2-1500 Style "S"	500	16	22	r/b
SLHOB0928B	2.25"	4.5"	Hobart SP-1500 SP-2-1500 Blank	500	16	22	
SLHOB0928TP	2.25"	4.5"	Hobart SP-1500 SP-2-1500 "S" T-Perfed	500	16	22	r/b
SLHOB0928BTP	2.25"	4.5"	Hobart SP-1500 SP-2-1500 Blank T-Perfed	500	16	22	
SLHOB0929TP	2.25"	4.5"	Hobart SP-1500 SP-2-1500	500	16	22	r/b
SLHOB0929BTP	2.25"	4.5"	Hobart SP-1500 SP-2-1500	500	16	22	
SLHOB0930	2.25"	3.0"	Hobart SP-2-1500 Style "U"	1500	16	40	r/b
SLHOB0930B	2.25"	3.0"	Hobart SP-2-1500 Blank	1500	16	40	
SLHOB0931	2.25"	4.5"	Hobart SP-2-1500 Style "W"	1000	16	40	r/b
SLHOB0931B	2.25"	4.5"	Hobart SP-2-1500 Blank	1000	16	40	
SLHOB0931TP	2.25"	4.5"	Hobart SP-2-1500 "W" T-Perfed	1000	16	40	r/b
SLHOB0931BTP	2.25"	4.5"	Hobart SP-2-1500 Blank T-Perfed	1000	16	40	
SLHOB0932B	2.25"	1.75"	Hobart Ultima 2000 Blank	4500	5	25	
SLHOB0933B	2.25"	2.375"	Hobart Ultima 2000 Blank	3350	5	25	
SHHOB0934	2.25"	3.0"	Hobart Ultima 2000 Safe Handling	2800	5	25	r/b
SLHOB0934B	2.25"	3.0"	Hobart Ultima 2000 Blank	2800	5	25	
SLHOB0934BTP	2.25"	3.0"	Hobart Ultima 2000 Blank T-Perfed	2800	5	25	
SLHOB0935B	2.25"	3.5"	Hobart Ultima 2000 Blank	2400	5	25	
SLHOB0936B	2.25"	4.5"	Hobart Ultima 2000 Blank	1900	5	25	
SLHOB0936BTP	2.25"	4.5"	Hobart Ultima 2000 Blank T-Perfed	1900	5	25	
SLISH1000P	40mm	36mm	Ishida Floral UPC Perfed	1000	12	12	purple
SLISH1000BP	40mm	36mm	Ishida Floral Blank Perfed	1000	12	12	
SLISH1001	64mm	37mm	Ishida Alpha Cosmic Non-UPC	1000	12	12	r/y
SLISH1001B	64mm	37mm	Ishida Alpha Cosmic Blank	1000	12	12	
SLISH1002	64mm	47mm	Ishida Alpha Cosmic UPC	800	12	13	r/y
SLISH1002G	64mm	47mm	Ishida Alpha Cosmic UPC	800	12	13	g/y
SLISH1002B	64mm	47mm	Ishida Alpha Cosmic Blank	800	12	13	
SLISH1003	64mm	59mm	Ishida AC Series	625	12	13	r/y
SLISH1003B	64mm	59mm	Ishida AC Series Blank	625	12	13	
SHISH1004	64mm	59mm	Ishida AC Series Red Triangle Safe Handli	625	12	13	r/b
SLISH1004B	64mm	59mm	Ishida AC Series Blank	625	12	13	
SLISH1005	64mm	67mm	Ishida AC Series Notched	500	12	13	red
SLISH1005B	64mm	67mm	Ishida AC Series Notched Blank	500	12	13	
SHISH1005	64mm	67mm	Ishida AC Series Notched Safe Hand	500	12	13	red
SLISH1006	64mm	73mm	Ishida AC Series	500	12	12	r/y
SLISH1006B	64mm	73mm	Ishida AC Series Blank	500	12	12	
SHISH1006	64mm	73mm	Ishida AC Series Safe Handling	500	12	12	r/y
SLISH1007	64mm	85mm	Ishida AC Series	450	12	13	r/y
SLISH1007B	64mm	85mm	Ishida AC Series Blank	450	12	13	
SHISH1007	64mm	85mm	Ishida AC Series Safe Handling	450	12	13	r/y
SLISH1008B	64mm	85mm	Ishida AC Series Blank	450	12	13	
SHISH1008	64mm	85mm	Ishida AC Series Safe Handling	450	12	13	r/b
SLISH1009P	64mm	93mm	Ishida AC Series UPC Perfed	400	12	12	r/y
SLISH1009BP	64mm	93mm	Ishida AC Series Blank Perfed	400	12	12	
SLISH1010B	60mm	85mm	Ishida AC Series Narrow Blank	425	12	12	
SLISH1011B	60mm	110mm	Ishida AC Series Narrow Blank	330	12	12	
SLISH1011BP	60mm	110mm	Ishida AC Series Narrow Blank Perfed	330	12	12	
SLISH1012B	64mm	110mm	Ishida AC Series Blank	330	12	12	
SLISH1012BP	64mm	110mm	Ishida AC Series Blank Perfed	330	12	12	

PSI Part#	Width	Length	Description	LPR	RPC	Lbs.	Hue
SLISH1013DP	64mm	145mm	Ishida AC Series Double Perfed	265	12	13	red
SLISH1013DPB	64mm	145mm	Ishida AC Series Double Perf Blank	265	12	13	
SLISH1014C	64mm	1560"	Ishida AC Series Continuous Strip	Cont.	12	13	
SLISH1015C	60mm	1560"	Ishida AC Series Narrow Cont. Strip	Cont.	12	12	
SLISH1016	64mm	73mm	Ishida DP-4000	2900	5	28	r/y
SLISH1016B	64mm	73mm	Ishida DP-4000 Blank	2900	5	28	
SHISH1016	64mm	73mm	Ishida DP-4000 Safe Handling	2900	5	28	r/y
SLISH1017	64mm	47mm	Ishida DP-4000 WPL-4000 UPC	4500	5	28	r/y
SLISH1017B	64mm	47mm	Ishida DP-4000 WPL-4000 Blank	4500	5	28	
SLISH1018	64mm	59mm	Ishida DP-4000 WPL-4000	3600	5	28	r/y
SLISH1018B	64mm	59mm	Ishida DP-4000 WPL-4000 Blank	3600	5	28	
SLISH1019B	64mm	59mm	Ishida DP-4000 WPL-4000 Blank	3600	5	28	
SHISH1019	64mm	59mm	Ishida DP-4000 WPL-4000 SH Triangle	3600	5	28	r/b
SLISH1020	64mm	85mm	Ishida DP-4000 WPL-4000 UPC	2500	5	28	r/y
SLISH1020B	64mm	85mm	Ishida DP-4000 WPL-4000 Blank	2500	5	28	
SHISH1020	64mm	85mm	Ishida DP-4000 WPL-4000 UPC SH	2500	5	28	r/y
SLISH1021B	64mm	85mm	Ishida DP-4000 WPL-4000 Blank	2500	5	28	
SHISH1021	64mm	85mm	Ishida DP-4000 WPL-4000 UPC SH	2500	5	28	r/b
SLISH1022	64mm	67mm	Ishida WPL-4000 Notched UPC	3150	5	28	red
SLISH1022B	64mm	67mm	Ishida WPL-4000 Notched Blank	3150	5	28	
SHISH1022	64mm	67mm	Ishida WPL-4000 Notched UPC SH	3150	5	28	red
SLKUB1100	64mm	37mm	Kubota FP-800 Non-UPC	1000	12	12	r/y
SLKUB1100B	64mm	37mm	Kubota FP-800 Blank	1000	12	12	
SLKUB1101	64mm	47mm	Kubota FP-800 UPC	800	12	13	r/y
SLKUB1101B	64mm	47mm	Kubota FP-800 Blank	800	12	13	
SLKUB1102	67mm	47.5mm	Kubota FP-900/910 UPC	1000	12	15	r/b
SLKUB1102B	67mm	47.5mm	Kubota FP-900/910 Blank	1000	12	15	
SLKUB1103	67mm	47.5mm	Kubota FP-900/910	1000	12	15	r/b
SLKUB1103B	67mm	47.5mm	Kubota FP-900/910 Blank	1000	12	15	
SLKUB1104	67mm	47.5mm	Kubota FP-900/910 Non-UPC	1000	12	15	r/b
SLKUB1104B	67mm	47.5mm	Kubota FP-900/910 Blank	1000	12	15	
SLKUB1105	67mm	50mm	Kubota FP-900/910/920 UPC	1000	12	16	r/b
SLKUB1105B	67mm	50mm	Kubota FP-900/910/920 Blank	1000	12	16	
SLKUB1106	67mm	60mm	Kubota FP-900/910/920 UPC	800	12	16	r/b
SLKUB1106B	67mm	60mm	Kubota FP-900/910/920 Blank	800	12	16	
SLKUB1107	67mm	60mm	Kubota FP-900/910/920 UPC Incred.	800	12	16	r/b
SLKUB1107B	67mm	60mm	Kubota FP-900/910/920 Blank	800	12	16	
SHKUB1107	67mm	60mm	Kubota FP-900/910/920 UPC Incred. SH	800	12	16	r/b
SLKUB1108	54mm	52.5mm	Kubota FP1-S UPC	940	12	13	r/b
SLKUB1108B	54mm	52.5mm	Kubota FP1-S Blank	940	12	13	
SLKUB1109B	54mm	72.5mm	Kubota FP1-S Blank	640	12	13	r/b
SHKUB1109	54mm	72.5mm	Kubota FP1-S UPC Safe Handling	640	12	13	
SLKUB1110C	56mm	1752"	Kubota FP1-S Continuous Strip	Cont.	12	13	
SLKUB1111	1.25"	2.625"	Kubota P-1 Thank You	1500	12	16	r/b
SLKUB1111B	1.25"	2.625"	Kubota P-1 Blank	1500	12	16	
SLNCI1200B	1"	3"	NCI Black Square	750	12	12	
SLNCI1201	2.46"	1.906"	NCI 1150/1151 UPC	2000	12	29	r/b
SLNCI1201B	2.46"	1.906"	NCI 1150/1151 Blank	2000	12	29	
SLNCI1202	2.46"	1.906"	NCI 3450 UPC	775	12	12	r/b
SLNCI1202B	2.46"	1.906"	NCI 3450 Blank	775	12	12	
SLNCI1203	2.46"	2.625"	NCI 3450 UPC Extended Text	540	12	12	r/b
SLNCI1203B	2.46"	2.625"	NCI 3450 UPC Extended Text	540	12	12	
SHNCI1203	2.46"	2.625"	NCI 3450 UPC Safe Handling	540	12	12	r/b
SLTEC1300	48mm	30mm	Tec H-1700	4500	5	13	y/b
SLTEC1300B	48mm	30mm	Tec H-1700 Blank	4500	5	13	

PSI Part#	Width	Length	Description	LPR	RPC	Lbs.	Hue
SLTEC1301	48mm	40mm	Tec H-1700	3400	5	15	y/b
SLTEC1301B	48mm	40mm	Tec H-1700 Blank	3400	5	15	
SLTEC1302	48mm	54.8mm	Tec H-1700	2500	5	15	y/b
SLTEC1302B	48mm	54.8mm	Tec H-1700 Blank	2500	5	15	
SLTEC1303	48mm	68.8mm	Tec H-1700	2000	5	17	y/b
SLTEC1303B	48mm	68.8mm	Tec H-1700 Blank	2000	5	17	
SHTEC1303	48mm	68.8mm	Tec H-1700 Safe Handling	2000	5	17	y/b
SLTEC1304P	48mm	76.2mm	Tec H-1700 Perfed	1800	5	13	y/b
SLTEC1304BP	48mm	76.2mm	Tec H-1700 Blank Perfed	1800	5	13	
SLTEC1305	48mm	84.1mm	Tec H-1700	1600	5	13	y/b
SLTEC1305B	48mm	84.1mm	Tec H-1700 Blank	1600	5	13	
SHTEC1305	48mm	84.1mm	Tec H-1700 Safe Handling	1600	5	13	y/b
SLTEC1306P	48mm	90.5mm	Tec H-1700 Perfed	1500	5	13	y/b
SLTEC1306BP	48mm	90.5mm	Tec H-1700 Blank Perfed	1500	5	13	
SLTEC1307	48mm	92mm	Tec H-1700	1500	5	13	y/b
SLTEC1307B	48mm	92mm	Tec H-1700 Blank	1500	5	13	
SHTEC1307	48mm	92mm	Tec H-1700 Safe Handling	1500	5	13	y/b
SLTEC1308	48mm	106.4mm	Tec H-1700	1300	5	13	y/b
SLTEC1308B	48mm	106.4mm	Tec H-1700 Blank	1300	5	13	
SHTEC1308	48mm	106.4mm	Tec H-1700 Safe Handling	1300	5	13	y/b
SLTEC1309P	48mm	112.7mm	Tec H-1700 Perfed	1200	5	13	y/b
SLTEC1309BP	48mm	112.7mm	Tec H-1700 Blank Perfed	1200	5	13	
SHTEC1309P	48mm	112.7mm	Tec H-1700 Perfed Safe Handling	1200	5	13	y/b
SLTEC1310P	48mm	139.7mm	Tec H-1700 Perfed	970	5	13	y/b
SLTEC1310BP	48mm	139.7mm	Tec H-1700 Blank Perfed	970	5	13	
SHTEC1310P	48mm	139.7mm	Tec H-1700 Perfed Safe Handling	970	5	13	y/b
SLTEC1311C	48mm	5340"	Tec H-1700 Continuous Strip	Cont.	5	13	
SLTEC1312	76mm	63.5mm	Tec H-18 7 Line Ingredient	1300	12	29	r/y
SLTEC1312B	76mm	63.5mm	Tec H-18 Blank	1300	12	29	
SHTEC1312	76mm	63.5mm	Tec H-18 Ingredient Safe Handling	1300	12	29	r/y
SLTEC1313	76mm	39.7mm	Tec HP-18 UPC	2000	12	28	r/y
SLTEC1313B	76mm	39.7mm	Tec HP-18 Blank	2000	12	28	
SLTEC1314	76mm	67.2mm	Tec HP-18 UPC Die Cut	1200	12	28	r/y
SLTEC1314B	76mm	67.2mm	Tec HP-18 Blank Die Cut	1200	12	28	
SHTEC1314	76mm	67.2mm	Tec HP-18 Die Cut Safe Handling	1200	12	28	r/y
SLTEC1315	57mm	63.5mm	Tec H-9100 UPC	3300	4	19	y/b
SLTEC1315B	57mm	63.5mm	Tec H-9100 Blank	3300	4	19	
SHTEC1315	57mm	63.5mm	Tec H-9100 Safe Handling	3300	4	19	y/b
SLTEC1316	57mm	92.8mm	Tec H-9100 UPC	2300	4	19	y/b
SLTEC1316B	57mm	92.8mm	Tec H-9100 Blank	2300	4	19	
SHTEC1316	57mm	92.8mm	Tec H-9100 Safe Handling	2300	4	19	y/b
SLTEC1317C	57mm	8464"	Tec H-9100 Continuous Strip	Cont.	4	19	
SLTEC1318	48mm	40mm	Tec SL-57-30 US UPC No Notch	600	16	10	y/b
SLTEC1318B	48mm	40mm	Tec SL-57-30 Blank No Notch	600	16	10	
SLTEC1319	60mm	30mm	Tec SL-59-30 Non-UPC	900	16	12	r/y
SLTEC1320	60mm	30mm	Tec SL-59-30 Non-UPC	900	16	12	y/b
SLTEC1320B	60mm	30mm	Tec SL-59-30 Blank	900	16	12	
SLTEC1321	60mm	40mm	Tec SL-59-30 UPC	700	16	12	r/y
SLTEC1322	60mm	40mm	Tec SL-59-30 UPC	700	16	12	y/b
SLTEC1322B	60mm	40mm	Tec SL-59-30 Blank	700	16	12	
SLTEC1323B	60mm	65mm	Tec SL-59-30 Blank	430	16	12	
SHTEC1323	60mm	65mm	Tec SL-59-30 UPC Safe Handling	430	16	12	r/y
SLTEC1324	48mm	30mm	Tec SL-66-30/6600 Non-UPC	900	16	10	y/b
SLTEC1325	48mm	30mm	Tec SL-66-30/6600 Non-UPC	900	16	10	r/y
SLTEC1324B	48mm	30mm	Tec SL-66-30/6600 Blank	900	16	10	

PSI Part#	Width	Length	Description	LPR	RPC	Lbs.	Hue
SLTEC1326	48mm	30mm	Tec SL-57-30 Non-UPC No Notch	900	16	10	y/b
SLTEC1327	48mm	40mm	Tec SL-66-30/6600 US UPC	600	16	10	y/b
SLTEC1328	48mm	40mm	Tec SL-66-30/6600 US UPC	600	16	10	r/y
SLTEC1327B	48mm	40mm	Tec SL-66-30/6600 Blank	600	16	10	
SLTEC1329P	48mm	76.2mm	Tec SL-66-30/6600 Perfed 6 line Ingred.	350	16	10	y/b
SLTEC1329BP	48mm	76.2mm	Tec SL-66-30/6600 Blank Perfed	350	16	10	
SLTEC1330P	48mm	90.5mm	Tec SL-66-30/6600 Perfed 12 line Ingred.	300	16	10	y/b
SLTEC1330BP	48mm	90.5mm	Tec SL-66-30/6600 Blank Perfed	300	16	10	
SLTEC1331P	48mm	112.7mn	Tec SL-66-30/6600 Perfed 22 line Ingred.	225	16	10	y/b
SLTEC1331BP	48mm	112.7mn	Tec SL-66-30/6600 Blank Perfed	225	16	10	
SHTEC1331P	48mm	112.7mn	Tec SL-66-30/6600 Perfed Ingred. SH	225	16	10	y/b
SLTEC1332	48mm	54.8mm	Tec SL-66-30/6600 Ctr. Code No Net Wt.	500	16	10	y/b
SLTEC1333	48mm	54.8mm	Tec SL-66-30/6600 Ctr. Code No Net Wt.	500	16	10	r/y
SLTEC1333B	48mm	54.8mm	Tec SL-66-30/6600 Blank	500	16	10	
SLTEC1334	48mm	68.8mm	Tec SL-66-30/6600 Ctr. Code No Net Wt.	400	16	10	blue
SHTEC1334	48mm	68.8mm	Tec SL-66-30/6600 Safe Handling Blue	400	16	10	blue
SLTEC1335	48mm	68.8mm	Tec SL-66-30/6600 Ctr. Code No Net Wt.	400	16	10	red
SHTEC1335	48mm	68.8mm	Tec SL-66-30/6600 Safe Handling Red	400	16	10	red
SHTEC1336	48mm	68.8mm	Tec SL-66-30/6600 Safe Handling Black	400	16	10	blk
SLTEC1335B	48mm	68.8mm	Tec SL-66-30/6600 Blank	400	16	10	
SLTEC1337	48mm	92mm	Tec SL-66-30/6600 Ctr. Code No Net Wt.	300	16	10	y/b
SLTEC1337B	48mm	92mm	Tec SL-66-30/6600 Blank	300	16	10	
SHTEC1337	48mm	92mm	Tec SL-66-30/6600 Safe Handling	300	16	10	y/b
SLTEC1338	48mm	68.8mm	Tec SL-66-30/6600 Bar Code Net Wt.	400	16	10	y/b
SLTEC1338B	48mm	68.8mm	Tec SL-66-30/6600 Blank	400	16	10	
SLTEC1339	48mm	82.6mm	Tec SL-66-30/6600 Bar Code Net Wt.	300	16	10	y/b
SLTEC1339B	48mm	82.6mm	Tec SL-66-30/6600 Blank	300	16	10	
SHTEC1339	48mm	82.6mm	Tec SL-66-30/6600 Safe Handling	300	16	10	y/b
SLTEC1340	48mm	84.1mm	Tec SL-66-30/6600 Bar Code Net Wt.	300	16	10	y/b
SLTEC1340B	48mm	84.1mm	Tec SL-66-30/6600 Blank	300	16	10	
SHTEC1340	48mm	84.1mm	Tec SL-66-30/6600 Safe Handling	300	16	10	y/b
SLTEC1341B	48mm	84.1mm	Tec SL-66-30/6600 Blank	300	16	10	
SHTEC1341	48mm	84.1mm	Tec SL-66-30/6600 Safe Handling	300	16	10	y/b
SLTEC1342	48mm	106.4mn	Tec SL-66-30/6600 Bar Code Net Wt.	250	16	10	y/b
SLTEC1342B	48mm	106.4mn	Tec SL-66-30/6600 Blank	250	16	10	
SHTEC1342	48mm	106.4mn	Tec SL-66-30/6600 Safe Handling	250	16	10	y/b
SLTEC1343	48mm	127mm	Tec SL-66-30/6600 34 Line No Net Wt.	200	16	10	y/b
SLTEC1343B	48mm	127mm	Tec SL-66-30/6600 Blank	200	16	10	
SHTEC1343	48mm	127mm	Tec SL-66-30/6600 Safe Handling	200	16	10	y/b
SLTEC1344C	48mm	1044"	Tec SL-66-30/6600 Continuous Strip	Cont.	16	10	
SLTEC1345	57mm	49.2mm	Tec SL-9000 UPC	600	16	13	y/b
SLTEC1345B	57mm	49.2mm	Tec SL-9000 Blank	600	16	13	
SLTEC1346	57mm	63.5mm	Tec SL-9000 UPC	450	16	13	y/b
SLTEC1346B	57mm	63.5mm	Tec SL-9000 Blank	450	16	13	
SHTEC1346	57mm	63.5mm	Tec SL-9000 Safe Handling	450	16	13	y/b
SHTEC1347	57mm	63.5mm	Tec SL-9000 Safe Handling Black	450	16	13	y/b/blk
SLTEC1348	57mm	92.8mm	Tec SL-9000 UPC	300	16	13	y/b
SLTEC1348B	57mm	92.8mm	Tec SL-9000 Blank	300	16	13	
SHTEC1348	57mm	92.8mm	Tec SL-9000 Safe Handling	300	16	13	y/b
SHTEC1349	57mm	92.8mm	Tec SL-9000 Safe Handling Black	300	16	13	y/b/blk
SLTEC1351	57mm	112.7mn	Tec SL-9000 UPC	250	16	13	y/b
SLTEC1351B	57mm	112.7mn	Tec SL-9000 Blank	250	16	13	
SHTEC1351	57mm	112.7mn	Tec SL-9000 Safe Handling Black	250	16	13	y/b/blk
SLTEC1352P	57mm	123.8mn	Tec SL-9000 Perf Ing. Bar Code Net Wt.	200	13	13	y/b
SLTEC1352BP	57mm	123.8mn	Tec SL-9000 Blank Perfed	200	13	13	

PSI Part#	Width	Length	Description	LPR	RPC	Lbs.	Hue
SLTEC1353C	57mm	1296"	Tec SL-9000 Continuous Strip	Cont.	16	13	
SLTOL1400BF	1.56"	.9687"	Toledo Direct Thermal Fluorescent Red	3000	10	12	red
SLTOL1401B	2.625"	1.5"	Toledo	700	10	10	
SLTOL1402	1"	3"	Toledo 301Red	1000	12	12	red
SLTOL1403	1"	3"	Toledo 301Blue	1000	12	12	blue
SLTOL1404	1"	3"	Toledo 301Green	1000	12	12	green
SLTOL1405B	1"	3"	Toledo 301Blank	1000	12	12	
SLTOL1406	1"	3"	Toledo 301M Modified	1000	12	12	red
SLTOL1406B	1"	3"	Toledo 301M Blank	1000	12	12	
SLTOL1407	1"	4"	Toledo 306/307	725	16	16	red
SLTOL1407B	1"	4"	Toledo 306/307 Blank	725	16	16	
SLTOL1408	1"	4"	Toledo 307M Modified	725	16	16	red
SLTOL1408B	1"	4"	Toledo 307M Blank	725	16	16	
SLTOL1409	2.625"	1.875"	Toledo 314 UL	4500	5	32	r/y
SLTOL1409B	2.625"	1.875"	Toledo 314 UL Blank	4500	5	32	
SLTOL1410	2.625"	1.719"	Toledo 314 UPC	5000	5	29	r/y
SLTOL1410B	2.625"	1.719"	Toledo 314 UPC Blank	5000	5	30	
SLTOL1411	2.625"	1.719"	Toledo 315 HL	5000	5	31	r/y
SLTOL1411B	2.625"	1.719"	Toledo 315 HL Blank	5000	5	32	
SLTOL1412	2.625"	1.96"	Toledo 315 UPC	4500	5	32	r/y
SLTOL1412B	2.625"	1.96"	Toledo 315 UPC Blank	4500	5	32	
SLTOL1413	2.625"	2.07"	Toledo 315 UL	4000	5	30	r/y
SLTOL1413B	2.625"	2.07"	Toledo 315 UL Blank	4000	5	30	
SLTOL1414	2.625"	2.375"	Toledo 315/317/355 ET	3800	5	31	r/y
SLTOL1414B	2.625"	2.375"	Toledo 315/317/355 ET Blank	3800	5	31	
SHTOL1414	2.625"	2.375"	Toledo 315/317/355 ET Safe Handling	3800	5	31	r/y
SLTOL1414P	2.625"	2.375"	Toledo 315/317/355 ET Perfed	3800	5	31	r/y
SLTOL1414BP	2.625"	2.375"	Toledo 315/317/355 ET Blank Perfed	3800	5	31	
SLTOL1415	2.625"	3.3125"	Toledo 315/317/355 ET	2700	5	31	r/y
SLTOL1415B	2.625"	3.3125"	Toledo 315/317/355 ET Blank	2700	5	31	
SHTOL1415	2.625"	3.3125"	Toledo 315/317/355 ET Safe Handling	2700	5	31	r/y
SLTOL1415P	2.625"	3.3125"	Toledo 315/317/355 ET Perfed	2700	5	31	r/y
SLTOL1415BP	2.625"	3.3125"	Toledo 315/317/355 ET Blank Perfed	2700	5	31	
SLTOL1416	2.625"	3.75"	Toledo 315/317/355 ET	2400	5	30	r/y
SLTOL1416B	2.625"	3.75"	Toledo 315/317/355 ET Blank	2400	5	30	
SHTOL1416	2.625"	3.75"	Toledo 315/317/355 ET Safe Handling	2400	5	30	r/y
SLTOL1416P	2.625"	3.75"	Toledo 315/317/355 ET Perfed	2400	5	30	r/y
SLTOL1416BP	2.625"	3.75"	Toledo 315/317/355 ET Blank Perfed	2400	5	30	
SLTOL1417	2.625"	4.25"	Toledo 315/317/355 ET	2100	5	30	r/y
SLTOL1417B	2.625"	4.25"	Toledo 315/317/355 ET Blank	2100	5	30	
SHTOL1417	2.625"	4.25"	Toledo 315/317/355 ET Safe Handling	2100	5	30	r/y
SLTOL1417P	2.625"	4.25"	Toledo 315/317/355 ET Perfed	2100	5	30	r/y
SLTOL1417BP	2.625"	4.25"	Toledo 315/317/355 ET Blank Perfed	2100	5	30	
SLTOL1418	2.625"	4.6875"	Toledo 315/317/355 ET	1950	5	30	r/y
SLTOL1418B	2.625"	4.6875"	Toledo 315/317/355 ET Blank	1950	5	30	
SHTOL1418	2.625"	4.6875"	Toledo 315/317/355 ET Safe Handling	1950	5	30	r/y
SLTOL1418P	2.625"	4.6875"	Toledo 315/317/355 ET Perfed	1950	5	30	r/y
SLTOL1418BP	2.625"	4.6875"	Toledo 315/317/355 ET Blank Perfed	1950	5	30	
SLTOL1419	2.625"	5.125"	Toledo 315/317/355 ET	1800	5	30	r/y
SLTOL1419B	2.625"	5.125"	Toledo 315/317/355 ET Blank	1800	5	30	
SHTOL1419	2.625"	5.125"	Toledo 315/317/355 ET Safe Handling	1800	5	30	r/y
SLTOL1419P	2.625"	5.125"	Toledo 315/317/355 ET Perfed	1800	5	30	r/y
SLTOL1419BP	2.625"	5.125"	Toledo 315/317/355 ET Blank Perfed	1800	5	30	
SLTOL1420	1.5625	2.968"	Toledo 324 UPC	1000	25	30	r/y
SLTOL1420B	1.5625	2.968"	Toledo 324 UPC Blank	1000	25	30	

PSI Part#	Width	Length	Description	LPR	RPC	Lbs.	Hue
SLTOL1421	2.625"	1.719"	Toledo 325 HL	600	30	26	r/y
SLTOL1421B	2.625"	1.719"	Toledo 325 HL Blank	600	30	26	
SLTOL1422	2.625"	1.5"	Toledo 325 HR	700	30	26	r/y
SLTOL1422B	2.625"	1.5"	Toledo 325 HR Blank	700	30	26	
SLTOL1423	2.625"	1.96"	Toledo 325 UPC	500	30	26	r/y
SLTOL1423B	2.625"	1.96"	Toledo 325 UPC Blank	500	30	26	
SLTOL1424	2.625"	2.07"	Toledo 325 UL	500	30	26	r/y
SLTOL1424B	2.625"	2.07"	Toledo 325 UL Blank	500	30	26	
SLTOL1425C	2.625"	1020"	Toledo 325/8425 Continuous Strip	Cont.	10	7	
SLTOL1426C	2.625"	1020"	Toledo 325/8425 Continuous Strip	Cont.	30	25	
SLTOL1427P	2.625"	3.75"	Toledo 325/8427 ET Thank You Perfed	325	30	27	blue
SLTOL1427BP	2.625"	3.75"	Toledo 325/8427 ET Blank Perfed	325	30	27	
SLTOL1428P	2.625"	4.25"	Toledo 325/8427 ET Thank You Perfed	300	30	27	blue
SLTOL1428BP	2.625"	4.25"	Toledo 325/8427 ET Blank Perfed	300	30	27	
SLTOL1429	2.625"	2.375"	Toledo 350/8450 UPC	1000	20	29	brown
SLTOL1429B	2.625"	2.375"	Toledo 350/8450 UPC Blank	1000	20	29	
SLTOL1429P	2.625"	2.375"	Toledo 350/8450 UPC Perfed	1000	20	29	brown
SLTOL1429BP	2.625"	2.375"	Toledo 350/8450 UPC Blank Perfed	1000	20	29	
SLTOL1430	2.625"	3.3125"	Toledo 350/8450 UPC	725	20	33	brown
SLTOL1430B	2.625"	3.3125"	Toledo 350/8450 UPC Blank	725	20	33	
SLTOL1430P	2.625"	3.3125"	Toledo 350/8450 UPC Perfed	725	20	33	brown
SLTOL1430BP	2.625"	3.3125"	Toledo 350/8450 UPC Blank Perfed	725	20	33	
SLTOL1431	2.625"	3.75"	Toledo 350/8450 UPC	650	20	33	brown
SLTOL1431B	2.625"	3.75"	Toledo 350/8450 UPC Blank	650	20	33	
SLTOL1431P	2.625"	3.75"	Toledo 350/8450 UPC Perfed	650	20	33	brown
SLTOL1431BP	2.625"	3.75"	Toledo 350/8450 UPC Blank Perfed	650	20	33	
SLTOL1432	2.625"	4.25"	Toledo 350/8450 UPC	600	20	30	brown
SLTOL1432B	2.625"	4.25"	Toledo 350/8450 UPC Blank	600	20	30	
SLTOL1432P	2.625"	4.25"	Toledo 350/8450 UPC Perfed	600	20	30	brown
SLTOL1432BP	2.625"	4.25"	Toledo 350/8450 UPC Blank Perfed	600	20	30	
SLTOL1433	2.625"	4.6875"	Toledo 350/8450 UPC	550	20	30	brown
SLTOL1433B	2.625"	4.6875"	Toledo 350/8450 UPC Blank	550	20	30	
SLTOL1433P	2.625"	4.6875"	Toledo 350/8450 UPC Perfed	550	20	30	brown
SLTOL1433BP	2.625"	4.6875"	Toledo 350/8450 UPC Blank Perfed	550	20	30	
SLTOL1434	2.625"	5.125"	Toledo 350/8450 UPC	500	20	31	brown
SLTOL1434B	2.625"	5.125"	Toledo 350/8450 UPC Blank	500	20	31	
SLTOL1434P	2.625"	5.125"	Toledo 350/8450 UPC Perfed	500	20	31	brown
SLTOL1434BP	2.625"	5.125"	Toledo 350/8450 UPC Blank Perfed	500	20	31	
SLTOL1435C	2.625"	2520"	Toledo 350/8450 Continuous Strip	Cont.	20	32	
SLTOL1436	2.625"	2.375"	Toledo 325/8460 ET	500	30	26	r/y
SLTOL1436B	2.625"	2.375"	Toledo 325/8460 ET Blank	500	30	26	
SHTOL1436	2.625"	2.375"	Toledo 325/8460 ET Safe Handling	500	30	26	r/y
SLTOL1436P	2.625"	2.375"	Toledo 325/8460 ET Perfed	500	30	26	r/y
SLTOL1436BP	2.625"	2.375"	Toledo 325/8460 ET Blank Perfed	500	30	26	
SLTOL1437	2.625"	3.3125"	Toledo 325/8460 ET	375	30	26	r/y
SLTOL1437B	2.625"	3.3125"	Toledo 325/8460 ET Blank	375	30	26	
SHTOL1437	2.625"	3.3125"	Toledo 325/8460 ET Safe Handling	375	30	26	r/y
SLTOL1437P	2.625"	3.3125"	Toledo 325/8460 ET Perfed	375	30	26	r/y
SLTOL1437BP	2.625"	3.3125"	Toledo 325/8460 ET Blank Perfed	375	30	26	
SLTOL1438	2.625"	3.75"	Toledo 325/8460 ET	325	30	26	r/y
SLTOL1438B	2.625"	3.75"	Toledo 325/8460 ET Blank	325	30	26	
SHTOL1438	2.625"	3.75"	Toledo 325/8460 ET Safe Handling	325	30	26	r/y
SLTOL1438P	2.625"	3.75"	Toledo 325/8460 ET Perfed	325	30	26	r/y
SLTOL1438BP	2.625"	3.75"	Toledo 325/8460 ET Blank Perfed	325	30	26	
SLTOL1439	2.625"	4.25"	Toledo 325/8460 ET	300	30	26	r/y

PSI Part#	Width	Length	Description	LPR	RPC	Lbs.	Hue
SLTOL1439B	2.625"	4.25"	Toledo 325/8460 ET Blank	300	30	26	
SHTOL1439	2.625"	4.25"	Toledo 325/8460 ET Safe Handling	300	30	26	r/y
SLTOL1439P	2.625"	4.25"	Toledo 325/8460 ET Perfed	300	30	26	r/y
SLTOL1439BP	2.625"	4.25"	Toledo 325/8460 ET Blank Perfed	300	30	26	
SLTOL1440	2.625"	4.6875"	Toledo 325/8460 ET	275	30	27	r/y
SLTOL1440B	2.625"	4.6875"	Toledo 325/8460 ET Blank	275	30	27	
SHTOL1440	2.625"	4.6875"	Toledo 325/8460 ET Safe Handling	275	30	27	r/y
SLTOL1440P	2.625"	4.6875"	Toledo 325/8460 ET Perfed	275	30	27	r/y
SLTOL1440BP	2.625"	4.6875"	Toledo 325/8460 ET Blank Perfed	275	30	27	
SLTOL1441	2.625"	5.125"	Toledo 325/8460 ET	250	30	27	r/y
SLTOL1441B	2.625"	5.125"	Toledo 325/8460 ET Blank	250	30	27	
SHTOL1441	2.625"	5.125"	Toledo 325/8460 ET Safe Handling	250	30	27	r/y
SLTOL1441P	2.625"	5.125"	Toledo 325/8460 ET Perfed	250	30	27	r/y
SLTOL1441BP	2.625"	5.125"	Toledo 325/8460 ET Blank Perfed	250	30	27	
SLTOL1442B	1.5625	2.156"	Toledo 8423 F-C Floral	550	30	16	
SLTOL1443C	1.5625	1200"	Toledo 8423 F-F Floral Continuous Strip	Cont.	10	15	
SLTOL1444B	2.3125	1.96"	Toledo 8442 UPC Blank	1140	20	26	
SLTOL1445	2.3125	2.375"	Toledo 8442 ET	925	20	26	r/y
SLTOL1445B	2.3125	2.375"	Toledo 8442 ET Blank	925	20	26	
SHTOL1445	2.3125	2.375"	Toledo 8442 ET Safe Handling	925	20	26	r/y
SLTOL1445P	2.3125	2.375"	Toledo 8442 ET Perfed	925	20	26	r/y
SLTOL1445BP	2.3125	2.375"	Toledo 8442 ET Blank Perfed	925	20	26	
SLTOL1446	2.3125	3.3125"	Toledo 8442 ET	675	20	26	r/y
SLTOL1446B	2.3125	3.3125"	Toledo 8442 ET Blank	675	20	26	
SHTOL1446	2.3125	3.3125"	Toledo 8442 ET Safe Handling	675	20	26	r/y
SLTOL1446P	2.3125	3.3125"	Toledo 8442 ET Perfed	675	20	26	r/y
SLTOL1446BP	2.3125	3.3125"	Toledo 8442 ET Blank Perfed	675	20	26	
SLTOL1447	2.3125	3.75"	Toledo 8442 ET	600	20	26	r/y
SLTOL1447B	2.3125	3.75"	Toledo 8442 ET Blank	600	20	26	
SHTOL1447	2.3125	3.75"	Toledo 8442 ET Safe Handling	600	20	26	r/y
SLTOL1447P	2.3125	3.75"	Toledo 8442 ET Perfed	600	20	26	r/y
SLTOL1447BP	2.3125	3.75"	Toledo 8442 ET Blank Perfed	600	20	26	
SLTOL1448B	2.625"	.971"	Toledo 8860-A Blank	900	10	10	
SLTOL1449B	2.625"	.971"	Toledo 8860-A-LC Blank	8500	5	28	
SLTOL1450B	2.625"	1.718"	Toledo 8860-B Blank	550	10	10	
SLTOL1451B	2.625"	1.718"	Toledo 8860-B-LC Blank	5000	5	28	
SLTOL1452B	2.625"	2.656"	Toledo 8860-C Blank	350	10	10	
SLTOL1453B	2.625"	2.656"	Toledo 8860-C-LC Blank	300	5	27	
SLTOL1454B	2.625"	3.875"	Toledo 8860-D Blank	250	10	10	
SLTOL1455B	2.625"	3.875"	Toledo 8860-D-LC Blank	2000	5	27	
SLWEL1500	68mm	46mm	Weldotron 5001E UPC	4000	3	15	r/b
SLWEL1500B	68mm	46mm	Weldotron 5001E Blank	4000	3	15	
SLWEL1501	68mm	46mm	Weldotron 5012 UPC	7000	3	28	r/b
SLWEL1501B	68mm	46mm	Weldotron 5012 Blank	7000	3	28	
SLWEL1502	68mm	46mm	Weldotron 5001E UPC Date	4000	3	15	r/b
SLWEL1502B	68mm	46mm	Weldotron 5001E Blank	4000	3	15	
SLWEL1503	68mm	46mm	Weldotron 5012 UPC Date	7000	3	28	r/b
SLWEL1503B	68mm	46mm	Weldotron 5012 Blank	7000	3	28	
SLWEL1504	60mm	43mm	Weldotron 9000 T-5 UPC 1.5" Core	4000	3	15	r/b
SLWEL1504B	60mm	43mm	Weldotron 9000 T-5 Blank 1.5" Core	4000	3	15	
SLWEL1505	60mm	43mm	Weldotron 9000 T-5 UPC 3" Core	3240	3	13	r/b
SLWEL1505B	60mm	43mm	Weldotron 9000 T-5 Blank 3" Core	3240	3	13	
SLWEL1506	60mm	55mm	Weldotron 9000 T-8 UPC 1.5" Core	3000	3	15	r/b
SLWEL1506B	60mm	55mm	Weldotron 9000 T-8 Blank 1.5" Core	3000	3	15	
SLWEL1507	60mm	55mm	Weldotron 9000 T-8 UPC 3" Core	2400	3	14	r/b

PSI Part#	Width	Length	Description	LPR	RPC	Lbs.	Hue
SLWEL1507B	60mm	55mm	Weldotron 9000 T-8 Blank 3" Core	2400	3	14	
SLWEL1508B	60mm	80mm	Weldotron 9000 Blank 1.5" Core	2200	3	15	
SHWEL1508	60mm	80mm	Weldotron 9000 Safe Handling 1.5" Core	2200	3	15	r/b
SLWEL1509B	60mm	80mm	Weldotron 9000 Blank 3" Core	1800	3	15	
SHWEL1509	60mm	80mm	Weldotron 9000 Safe Handling 3" Core	1800	3	15	r/b
SHHAP1600	2.25"	1.25"	Safe Handling Hand Applied Black	1000	20	25	blk
SHHAP1601	2.25"	1.25"	Safe Handling Hand Applied Red	1000	20	25	red